

Technical Data

FLIR i3

Part number:

39301-0403

Copyright

© 2011, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

February 03, 2011, 09:15 AM

Corporate Headquarters

FLIR Systems, Inc. 27700 SW Parkway Ave. Wilsonville, OR 97070

Telephone: +1-503-498-3547

Website

http://www.flir.com

Customer support

http://support.flir.com

Legal disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply.

Information and equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited.

FLIR Commercial Systems B.V.

Charles Petitweg 21 4847 NW Breda The Netherlands

Phone: +31 (0) 765 79 41 94 Fax: +31 (0) 765 79 41 99 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Systems Sweden Phone: +46 (0)8 753 25 00 Fax: +46 (0)8 753 23 64 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Systems Germany

Phone: +49 (0)69 95 00 900 Fax: +49 (0)69 95 00 9040 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Advanced Thermal Solutions France

Phone: +33 (0)1 41 33 97 97 Fax: +33 (0)1 64 11 37 55 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Systems UK

Phone: +44 (0) 1732 220 011 Fax: +44 (0) 1732 220 014 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Systems Italy Phone: +39 (0)2 99 45 10 01 Fax: +39 (0)2 99 69 24 08 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Systems Spain Phone: +34 91 490 40 60 Fax: +34 91 662 97 48 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Systems Middle East Phone: +971 4 299 6898

Fax: +971 4 299 6895 E-mail: flir@flir.com Web: http://www.flir.com

FLIR Systems Belgium Phone: +32 (0)3 287 87 10

Fax: +32 (0)3 287 87 29 E-mail: flir@flir.com Web: http://www.flir.com



Affordable infrared camera with high quality image, high accuracy, focus free viewing, and storage on miniSD card.

Key features:

- Extremely lightweight, 0.34 kg (0.75 lb.)
- 2% high accuracy and thermal sensitivity of 0.15°C Large 2.8 in. color LCD with quality images saved on miniSD card
- Long, 5 hour battery life
- Focus free lens for quick and convenient viewing

Imaging and optical data

Field of view (FOV)	12.5° × 12.5°
Minimum focus distance	0.6 m (2 ft.)
Spatial resolution (IFOV)	3.7 mrad
F-number	1.5
Thermal sensitivity/NETD	< 0.15°C (0.27°F) / 150 mK
Image frequency	9 Hz
Focus	Focus free

Detector data

Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	7.5–13 μm
IR resolution	60 × 60 pixels

Image presentation

Display	2.8 in. color LCD
Image adjustment	Automatic adjust/lock image

Measurement

Object temperature range	-20°C to +250°C (-4°F to +482°F)
Accuracy	±2°C (±3.6°F) or ±2% of reading, for ambient temperature 10°C to 35°C (+50°F to 95°F)

Measurement analysis

Spotmeter	Center spot
Emissivity correction	Variable from 0.1 to 1.0
Emissivity table	Emissivity table of predefined materials
Reflected apparent temperature correction	Automatic, based on input of reflected temperature

Set-up

Color palettes	Black and white, iron and rainbow

Page 1 (of 13) http://www.flir.com

FLIR i3

P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

Set-up	
Set-up commands	Local adaptation of units, language, date and time formats
Storage of images	
Storage media	miniSD card
File formats	Standard JPEG, 14-bit measurement data included
Data communication interfaces	
Interfaces	USB Mini-B: Data transfer to and from PC
Power system	
Battery type	Rechargeable Li Ion battery
Battery voltage	3.6 V
Battery operating time	Approx. 5 hours at +25°C (+77°F) ambient temperature and typical use
Charging system	Battery is charged inside the camera.
Charging time	3 h to 90% capacity
Power management	Automatic shut-down
AC operation	AC adapter, 90–260 VAC input, 5 VDC output to camera
Environmental data	
Operating temperature range	0°C to +50°C (+32°F to +122°F)
Storage temperature range	-40°C to +70°C (-40°F to +158°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95% relative humidity
EMC	 EN 61000-6-2:2005 (Immunity) EN 61000-6-3:2007 (Emission) FCC 47 CFR Part 15 Class B (Emission)
Encapsulation	Camera housing and lens: IP 43 (IEC 60529)
Bump	25 g (IEC 60068-2-29)
Vibration	2 g (IEC 60068-2-6)
Physical data	
Camera weight, incl. battery	0.34 kg (0.75 lb.)
Camera size (L × W × H)	223 × 79 × 83 mm (8.8 × 3.1 × 3.3 in.)
Material	Polycarbonate + acrylonitrile butadiene styrene (PC-ABS) Thixomold magnesium Thermoplastic elastomer (TPE)
Color	Blue and gray
Certifications	
Certification	UL, CSA, CE, PSE and CCC
Scope of delivery	
Packaging, type	Hard case
Hard transport case (including padlock) Infrared camera Battery (inside camera) Calibration certificate FLIR QuickReport CD Hand strap miniSD card, with SD card adapter Power supply/charger with EU, UK, US and Aust Printed Getting Started Guide Printed Important Information Guide USB cable	ralian plugs

- USB cable
 User documentation CD-ROM

Optional Accessories

- T910737 Memory card micro-SD with adapters
 1910423 USB cable Std A <-> Mini-B
- T910711 Power supply/charger with EU, UK, US and AU plugs

FLIR i3

P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

Optional Accessories

- T126024 Pouch T197619 Hard transport case for ix
- T197410 Battery

Optional Software

- T197717 FLIR Reporter 8.5 SP2, Professional
 T197717L5 FLIR Reporter 8.5 SP2, Professional, 5 user licenses
 T197717L10 FLIR Reporter 8.5 SP2, Professional, 10 user licenses
 T197778 FLIR BuildIR 2.1
 T197778L5 FLIR BuildIR 2.1, 5 user licenses
 T197778L10 FLIR BuildIR 2.1, 10 user licenses



Optional Accessories

P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

T910737; Memory card micro-SD with adapters



General description

Micro-SD Card for data storage (e.g. images)

Technical data

Memory card, size At least 2 GB

Scope of delivery

- Adapter to miniSD Card
 Adapter from miniSD Card to SD memory card

v1.03

1910423; USB cable Std A <-> Mini-B



General description

This cable is used to connect the infrared camera with a computer, using the USB protocol.

Technical data

Weight	60 g (2.1 oz.)
Cable length	1.8 m (5.9 ft.)
Connector	Standard USB-A to USB Mini-B
	v1.



Optional Accessories

P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

T910711; Power supply/charger with EU, UK, US and AU plugs



General description

Combined power supply & battery charger.

Technical data

AC operation	100-240 VAC, 50/60 Hz, output 5.0 VDC, 1.2 A
Power	6 W
Size (L × W × H)	69.2 × 43.3 × 29.8 mm (2.7 × 1.7 × 1.2 in.)
Cable length	1.8 m (5.9 ft.)

Scope of delivery

- Power supply/Battery charger EU, UK, US and Australian plugs

v1.02

T126024; Pouch



Camera pouch for FLIR iX series with shoulder strap (1.4 m, 4.6 ft.), possible to attach to waist belt.

Technical data

Weight	0.12 kg (0.26 lb.)
Size $(L \times W \times H)$	$240 \times 90 \times 75$ mm (9.4 \times 3.5 \times 3.0 in.)
Color	Black
	v1.0



Optional Accessories

P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

T197619; Hard transport case for ix



General description

Hard transport case for FLIR iX and Extech iX

Technical data

Weight	1.69 kg (3.73 lb.)
Size $(L \times W \times H)$	390 × 330 × 120 mm (15.4 × 13.0 × 4.7 in.)
Color	Black
	v1.0

T197410; Battery



General description

High capacity battery for the IR camera.

Technical data


Battery type	Rechargeable Li Ion battery
Battery voltage	3.6 V
Battery note	Approximate lithium content: 0.7 g
Charging system	Battery is charged inside the camera
	v1.01



P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

T197717; FLIR Reporter 8.5 SP2, Professional



FLIR Reporter Professional is a powerful software for creating compelling and professional, fully customized, easy-tointerpret maintenance reports

Professional Report Wizard guides you step-by-step in combining all IR inspection data - infrared and visual images, temperature measurements, and text notes - into a professional, easy-to-interpret maintenance report.

- Flexible report page design and layout for customized reports
- Use quick insert function to easily create custom report pages Fully integrated with standard Microsoft Word
- Generates reports in standard MS Office format and PDF-format
- Powerful temperature analysis
- Triple Fusion Picture-in-Picture (movable, sizable, scalable)
- Rapid report manager supporting automatic report generation by drag-and-drop
- Trending functionality
- Automatic link to Google™ Maps for images with GPS coordinates
- Automatic summary table for the report
- Fine tune images and make full temperature analysis directly in Microsoft Word Spell check
- Create your own formulas including measurement values from images
- Play radiometric sequences directly in the report Search functionality to quickly finding images for your report
- Panorama tool for combining several images to a larger image
- Support for GF series IR images
- Auto Update function
- Office 2003 (32-bit), Office 2007 (32-bit) and Office 2010 (32-bit)
- Windows 7 (32 and 64-bit), Windows Vista (32 and 64-bit) Support for MeterLink™ data
- *.docx compatibility

Download

http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=93

Release notes

Version	8.5 SP2
New features	 News in SP2: Office 2010 (32 bit) Minor bug fixes News in SP1: Full support for Windows® 7 Support for MeterLink™ data *.docx compatibility

Scope of delivery

- FLIR Reporter Professional
- Getting Starting Guide

Page 7 (of 13) http://www.flir.com



P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

System requirements


Operating system

- Windows XP, 32-bit
- Windows Vista, 32-bit
- Windows Vista, 64-bit Windows 7, 32-bit

Windows 7, 64-bit

v1.03

T197717L5; FLIR Reporter 8.5 SP2, Professional, 5 user licenses



General description

FLIR Reporter Professional is a powerful software for creating compelling and professional, fully customized, easy-to-

Professional Report Wizard guides you step-by-step in combining all IR inspection data - infrared and visual images, temperature measurements, and text notes - into a professional, easy-to-interpret maintenance report.

- Flexible report page design and layout for customized reports
- Use quick insert function to easily create custom report pages Fully integrated with standard Microsoft Word
- Generates reports in standard MS Office format and PDF-format
- Powerful temperature analysis
 Triple Fusion Picture-in-Picture (movable, sizable, scalable)
- Rapid report manager supporting automatic report generation by drag-and-drop
- Trending functionality Automatic link to Google™ Maps for images with GPS coordinates
- Automatic summary table for the report
- Fine tune images and make full temperature analysis directly in Microsoft Word Spell check
- Create your own formulas including measurement values from images Play radiometric sequences directly in the report
- Search functionality to quickly finding images for your report Panorama tool for combining several images to a larger image
- Support for GF series IR images
- Auto Update function
 Office 2003 (32-bit), Office 2007 (32-bit) and Office 2010 (32-bit)
- Windows 7 (32 and 64-bit), Windows Vista (32 and 64-bit)
 Support for MeterLink™ data
 *.docx compatibility

 $\underline{\text{http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=93}}$

Release notes

Version 8.5 SP2

Page 8 (of 13)



P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

Release notes

New features

- --- News in SP2:
- Office 2010 (32 bit)
- Minor bug fixes --- News in SP1:
- Full support for Windows® 7 Support for MeterLink™ data *.docx compatibility

Scope of delivery

- FLIR Reporter Professional Getting Starting Guide 5 user licenses


System requirements

Operating system

- Windows XP, 32-bit
- Windows Vista, 32-bit
- Windows Vista, 64-bit Windows 7, 32-bit
- Windows 7, 64-bit

v1.02

T197717L10; FLIR Reporter 8.5 SP2, Professional, 10 user licenses



General description

FLIR Reporter Professional is a powerful software for creating compelling and professional, fully customized, easy-tointerpret maintenance reports.

Professional Report Wizard guides you step-by-step in combining all IR inspection data - infrared and visual images, temperature measurements, and text notes – into a professional, easy-to-interpret maintenance report.

Key features:



P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

General description

- Flexible report page design and layout for customized reports
- Use quick insert function to easily create custom report pages Fully integrated with standard Microsoft Word Generates reports in standard MS Office format and PDF-format

- Powerful temperature analysis
 Triple Fusion Picture-in-Picture (movable, sizable, scalable)
 Rapid report manager supporting automatic report generation by drag-and-drop
- Trending functionality
- Automatic link to Google™ Maps for images with GPS coordinates Automatic summary table for the report
- Fine tune images and make full temperature analysis directly in Microsoft Word
- Spell check Create your own formulas including measurement values from images Play radiometric sequences directly in the report

- Search functionality to quickly finding images for your report Panorama tool for combining several images to a larger image Support for GF series IR images

- Auto Update function
 Office 2003 (32-bit), Office 2007 (32-bit) and Office 2010 (32-bit)
- Windows 7 (32 and 64-bit), Windows Vista (32 and 64-bit)
 Support for MeterLink™ data
 *.docx compatibility

 $\underline{\text{http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=93}}$

Release notes

Version	8.5 SP2
New features	 News in SP2: Office 2010 (32 bit) Minor bug fixes News in SP1: Full support for Windows® 7 Support for MeterLink™ data *.docx compatibility

Scope of delivery

- FLIR Reporter Professional
- Getting Starting Guide
- 10 user licenses

System requirements


Operating system	 Windows XP, 32-bit 	
	 Windows Vista, 32-bit 	
	 Windows Vista, 64-bit 	
	 Windows 7, 32-bit 	
	 Windows 7, 64-bit 	



P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

T197778; FLIR BuildIR 2.1



General description

A dedicated and flexible software for advanced analyses of building related applications.

Report templates for energy loss / cost savings potential, air infiltration, moisture and insulation deficiencies. Assess scope of damage/problem.

Increase Speed & Quality of your reports.

Quantify geometrical areas and use the panorama tool to stitch images of large objects together. Makes the work considerably easier for building related analyses - Organize, Analyze, Report

- See, Quantify and Estimate potential energy cost savings.

 Possibility of assessing scope of damage/problem

 Customized report templates for: Air infiltration, Moisture, Insulation deficiencies, and estimation of potential energy Panorama functionality: Create automatically one image from many to cover large objects or increase resolution

- Create graph of the conditions during the inspection. Support for MeterLink™ data

http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=87

Release notes

Version	FLIR BuildIR 2.1
New features	 Support for Windows® 7 Support for MeterLink™ data Support for fusion

Scope of delivery

FLIR BuildIR		
System requirements		
Operating system	Windows XP, 32-bitWindows Vista, 32-bit/64-bitWindows 7, 32-bit/64-bit	
		v1.01

Page 11 (of 13) http://www.flir.com



P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

T197778L5; FLIR BuildIR 2.1, 5 user licenses



General description

A dedicated and flexible software for advanced analyses of building related applications.

Report templates for energy loss / cost savings potential, air infiltration, moisture and insulation deficiencies. Assess scope of damage/problem.

Increase Speed & Quality of your reports.

Quantify geometrical areas and use the panorama tool to stitch images of large objects together. Makes the work considerably easier for building related analyses - Organize, Analyze, Report

- See, Quantify and Estimate potential energy cost savings.

 Possibility of assessing scope of damage/problem

 Customized report templates for: Air infiltration, Moisture, Insulation deficiencies, and estimation of potential energy Panorama functionality: Create automatically one image from many to cover large objects or increase resolution

- Create graph of the conditions during the inspection. Support for MeterLink™ data

http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=87

Release notes

Version	FLIR BuildIR 2.1
New features	 Support for Windows® 7 Support for MeterLink™ data Support for fusion

Scope of delivery

- FLIR BuildIR
- 5 user licenses

System requirements

Operating system	Windows XP, 32-bitWindows Vista, 32-bit/64-bitWindows 7, 32-bit/64-bit	
		v1.01

Page 12 (of 13)



P/N: 39301-0403

© 2011, FLIR Systems, Inc. All rights reserved worldwide.

T197778L10; FLIR BuildIR 2.1, 10 user licenses



General description

A dedicated and flexible software for advanced analyses of building related applications.

Report templates for energy loss / cost savings potential, air infiltration, moisture and insulation deficiencies. Assess scope of damage/problem.

Increase Speed & Quality of your reports.

Quantify geometrical areas and use the panorama tool to stitch images of large objects together. Makes the work considerably easier for building related analyses - Organize, Analyze, Report

- See, Quantify and Estimate potential energy cost savings.

 Possibility of assessing scope of damage/problem

 Customized report templates for: Air infiltration, Moisture, Insulation deficiencies, and estimation of potential energy Panorama functionality: Create automatically one image from many to cover large objects or increase resolution

- Create graph of the conditions during the inspection. Support for MeterLink™ data

http://support.flir.com/SwDownload/app/RssSWDownload.aspx?ID=87

Release notes

Version	FLIR BuildIR 2.1
New features	 Support for Windows® 7 Support for MeterLink™ data Support for fusion

Scope of delivery

- FLIR BuildIR
- 10 user licenses

Operating system	 Windows XP, 32-bit
3 -7	 Windows Vista, 32-bit/64-bit
	 Windows 7, 32-bit/64-bit

Page 13 (of 13)