



PIH 5040S / 5063 / 5064 / 5067

Housing & Bracket

Housing

Indoor Housing		
		
Model No.	PIH-5040S	PIH-5063
Mounting	Bottom	
Material	Aluminum	Aluminum (IK10)
Window Dimension (mm) / Glass Thickness	74(W) x 64 (H) / 5mm	Φ110 Heat Resistant Glass / 5mm
Dimension (mm)	140mm(W) x 115mm(H) x 373mm(D)	Housing: Φ134 x 318mm (L) Bracket: 211.5mm (L)
Weight	1.3kg	2.0kg
Ext. Model	-	PIH-5063: AC230V (Heater & Blower) PIH-5064: AC24V (Heater & Blower) PIH-5067: AC117V (Heater & Blower)



PRH 5480/5880 / PRH 5480M/5880M / PRH 54200/58200 / PRH 9480/9880

Infrared Illuminator Housing

		Infrared Illuminator Housing						Invisible Infrared Illuminator Housing	
									
Model No.		PRH-5480	PRH-5880	PRH-5480M	PRH-5880M	PRH-54200	PRH-58200	PRH-9480	PRH-9880
Power Input Voltage		AC24V ±10%	AC90 – 260V max.	AC24V ±10%	AC90 – 260V max.	AC24V ±10%	AC90 – 260V max.	AC24V ±10%	AC90 – 260V max.
Radiant Distance		100m		60m		200m		80m	
Window		Φ110 Heat Resistant Glass							
Glass Thickness		3mm							
Infrared LED	Wave Length	850nm						940nm	
	Angle	15° + 25°		30°		6° + 30°			
	Quantity	5 units (15°) + 2 units (25°)		17 units		5 units (6°) + 2 units (30°)			
	Power On	Sensor Auto Control, Adjustable Control Point							
Blower Control		On: 35°C Off: 25°C							
Heater Control		On: 15°C Off: 25°C							
Suitable Camera and Lens		Max. 200mm length							
IP Rating		IP66							
Mounting		Bottom							
Material		Aluminum (IK10)							
Power Consumption		22W				32W			
Operating Temperature		-40°C – + 60°C (-40°F – + 140°F)							
Dimension		Housing : Φ134 x 318mm (L), Bracket : 211.5mm (L)							
Weight		3500g							



PIH 500 / 500L / 5001N / 5002L / 5005M / PIH 5004 / 5004L

Housing & Bracket

Camera Bracket

Camera Bracket				
				
Model No.	PIH-500	PIH-500L	PIH-5001N	PIH-5002L
Adjustment	Pan: 360° Tilt: ±90°			Pan & Tilt
Maximum Load	2kg			6kg
Construction	ABS Injection		Aluminum	
Dimension(mm)	76 (W) x 153 (H) x 73 (D)	76 (W) x 218 (H) x 73 (D)	123 (L) x 45 (Φ)	202 (W) x 252 (H) x 24 (D)x 119 (Φ)
Weight	80g	100g	110g	700g


Camera Bracket			
			
Model No.	PIH-5005M	PIH-5004	PIH-5004L
Adjustment	Pan: 360° Tilt: ±90°	Pan & Tilt	Pan & Tilt
Maximum Load	5kg	10kg	10kg
Construction	Aluminum	Aluminum, Light Gray Textured	
Dimension(mm)	164 (L) x 119 (Φ)	85 (W) x 309 (H) x 99 (D)	61 (W) x 240 (H) x 83 (D)
Weight	280g	600g	300g



PIH-WM / PIH-26WM / BTR01S / BTR03S / PIH-5003 / BTS02S / BCD01S

Bracket

Bracket				
				
Name	Bracket			
Model No.	PIH-WM	PIH-26WM	BTR01S	BTR03S
Adjustment	-	-	Pan & Tilt	-
Maximum Load	5kg	2kg	10kg	2kg
Construction	Aluminum	ABS Injection	Aluminum	Steel, Light Gray Texture
Dimension(mm)	132 (W) x 111 (H) x 169 (D)	120 (W) x 65 (H) x 144 (D)	262 (W) x 287 (H) x 39 (D)	200 (W) x 50 (H) x 52 (D)
Weight	600g	95g	1000g	3000g

Bracket			
			
Name	Scanner Bracket	Corner & Pole Mount	Pendant Mount
Model No.	PIH-5003	BTS02S	BCD01S
Adjustment	Pan	-	-
Maximum Load	10kg	15kg	-
Construction	Aluminum, Light Gray Textured	Aluminum	Aluminum
Dimension(mm)	85 (W) x 309 (H) x 99 (D)	190(W) x 130 (H) x 105 (D)	Ø145 x 37 mm
Weight	450g	500g	310g



PIH 303B / 303PEX / 303P / PIH-510 CPM / PIH Z6 / PIH 520HB /

Bracket

Bracket						
Name	Wall Mount	Extension Tube	Pendant Mount	Corner & Pole Mount	Extension Tube	Pendant Mount
Model No.	PIH-303B	PIH-303PEX	PIH-303P	PIH-510 CPM	PIH-Z6	PIH-520HB
Maximum Load	30kg	-	30kg	25kg	-	-
Construction	Aluminum, Light Gray Textured					
Dimension(mm)	148(W) × 385 (H) × 175 (D)	300(H)	148(W) × 385 (H) × 175 (D)	275(W) × 91 (H) × 182(D)	300(H)	284(L)×204(W) ×149.5(H)
Weight	1.2kg	-	1.1kg	0.5kg	-	2.7Kg
Schematic Drawing		-			-	
Matched Model	SP9364 / SP9368 SP9264 / SP9268 ST9364 / ST9368 ST9264 / ST9268	SP9364 / SP9368 SP9264 / SP9268 ST9364 / ST9368 ST9264 / ST9268	SP9364 / SP9368 SP9264 / SP9268 ST9364 / ST9368 ST9264 / ST9268	PIH 520LB PIH 510L	PIH 7625DW	SP8364 / SP8368 SP8264 / SP8268 ST8364 / ST8368 ST8264 / ST8268

PIH-510 CPM : Stainless Strap for Pole X2 Diameter Range 2.5–7Inch



PIH76WM / PIH 303BX / PIH 520L / 520LB / CPM / PIH 520G

Bracket

Bracket						
Name	Wall Mount	Wall Mount	Wall Mount	Wall Mount	Corner & Pole Mount	Swan Neck
Model No.	PIH-76WM	PIH-303BX	PIH-520L	PIH-520LB	PIH-CPM	PIH-520G
Maximum Load	5kg	30kg	-	-	20kg	-
Construction	Aluminum	Steel, Light Gray Texture	Aluminum			Steel
Dimension(mm)	150(W) ×110 (H) × 171 (D)	180(W) × 318.5 (H) × 214 (D)	100(W) ×160 (H) × 210(D)	204(W) ×284(H) × 255(D)	156.6(W) ×126 (H) × 86.8(D)	725(L)×455(W) ×83(H)mm
Weight	0.5kg	3.9k	0.84kg	3.1kg	0.44kg	6.8kg
Schematic Drawing						
Matched Model	SP9364 / SP9368 SP9264 / SP9268 ST9364 / ST9368 ST9264 / ST9268	PIH 7625DW	ST8364 / ST8368 ST8264 / ST8268	ST8364 / ST8368 ST8264 / ST8268	PIH 520L / PIH CPM PIH 5004 / 5004L	ST8364 / ST8368 ST8264 / ST8268