

Net-C CW-1308B Cable



Telephone cable to standard BT specification suitable for use externally and within buildings. As standard it is available from 10pair to 320 pair and is normally supplied with a 1.38mm cream earth wire as standard. The sheath is black LSZH and has the addition of an Aluminium/Polyethylene laminate tape which is bonded to the sheath. This provides an effective moisture barrier. The cables are metre marked for ease of use during installation.

Technical Specifications	
Standards	CW1308 - IEC 60754-1
Conductor	Class 1 solid annealed plain copper
Insulation	PVC (Polyvinyl Chloride)
Separator	Polyester wrapping tape
Screen	Al/PE (Aluminium/Polyethylene) tape
Sheath	LSZH (Low Smoke Zero Halogen)
Colour	Black
Temperature Rating	0°C to +70°C
Minimum Bending Radius	15 x overall diameter

Part Number	Description
NC-CW1308B-10E	10 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-20E	20 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-50E	50 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-100E	100 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-200E	200 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK
NC-CW1308B-320E	320 PAIR + E INTERNAL/EXTERNAL CABLE LSF BLACK

Net-C CW-1308B Cable



Cable Dimensions

No of pairs	Conductor	Weight KM/KG	Cable diameter (MM)
10	0.5mm	98	7
20	0.5mm	155	9
50	0.5mm	325	13.5
100	0.5mm	610	19
200	0.5mm	1155	25.6
320	0.5mm	1725	32.5

Insulation Colour Code

Pair	Colour	
	A Wire	B Wire
1	White	Blue
2	White	Orange
3	White	Green
4	White	Brown
5	White	Grey
6	Red	Blue
7	Red	Orange
8	Red	Green
9	Red	Brown
10	Red	Grey

Binders Colour Code

Unit Number	1	2	3	4	5	6	7	8	9	10
Colour	Blue	Orange	Green	Brown	Grey	White	Red	Black	Yellow	Violet