

NeTYS PE

from 600 to 2000 VA

practical and cost-effective UPS



NeTYS PE
600/650/850 VA

NeTYS PE
1000 VA

NeTYS PE
1500/2000 VA

Technology

- > Line interactive technology with AVR - step wave



Technical data

NeTYS PE						
Sn	600 VA	650 VA	850 VA	1000 VA	1500 VA	2000 VA
Pn	360 W	360 W	480 W	600 W	900 W	1200 W
Input/output	1/1					
INPUT						
Rated voltage	230 V					
Voltage tolerance	170 - 280 V					
Rated frequency	50/60 Hz with automatic selection					
Mains connection	IEC320 socket					
OUTPUT						
Automatic Voltage Regulation (AVR)	•	•	•	•	•	•
Rated voltage	230 V ±10%					
Rated frequency	50/60 Hz					
Wave form	Step wave					
Protection	Overload, significant discharge and short circuit					
Connections	4 x IEC 320 (C13) ⁽¹⁾				6 x IEC 320 (C13) ⁽¹⁾	
BATTERIES						
Type	Sealed lead-acid maintenance free - expected life 3/5 years					
Back-up time ⁽²⁾	15 min	15 min	20 min	45 min	55 min	60 min
COMMUNICATION						
Interface	-	USB				
Local communication software	-	Local View				
Data line protection	-	NTP data line suppressor				
UPS CABINET						
Dimensions W x D x H	100 x 290 x 145 mm		145 x 345 x 165 mm		145 x 390 x 205 mm	
Weight	5.0 kg	5.2 kg	6.0 kg	9.7 kg	11.2 kg	12 kg
STANDARDS						
Safety	EN 62040-1, AS 62040-1					
EMC	EN 62040-2, AS 62040-2					
Product certification	C-Tick (N876)					

(1) Australian standard sockets on Netys PE models specific for Australia.

(2) PC + 17" LCD monitor.

The solution for

- CAD, graphic workstations
- Multimedia workstations and peripherals
- LCD screens and monitors
- POS (Point Of Sales)

Standard communication features

- **LOCAL VIEW:** ideal UPS monitoring and shutdown point-to-point solution for Windows®, Linux and Mac OS X operating systems.

Please allow an additional 250mm depth for cabling an installed UPS when specifying your cabinet