




Wireless LAN enabled
High Definition Core Monitoring fusion splicer

TYPE-71C+



Rapid, Elite, Connected

Faster Splicing 6sec / Heating 14sec
Splicing loss SMF 0.01dB (Typical)



Fully Optimized
Two Independent
Heaters for
High Productivity



Wireless LAN
Connectivity & Useful
Smart Phone App



Touch Screen
Control Panel



Durable & Rugged

Specifications		
Items		TYPE-71C+
Optical fibre requirements	Material	Silica glass
	Fibre count / Profile types	Single / SMF(G.652), MMF(G.651), DSF(G.653), NZDSF(G.655), BIF(G.657), EDF
	Fibre diameter	Cladding diameter : 80 ~ 150µm, Coating diameter : 100 ~ 1,000µm
	Cleave length	5 ~ 16mm with coating clamp
Standard performance	Splice loss (typical)*1	SMF : 0.01dB, MMF : 0.01dB, DSF : 0.03dB, NZDSF : 0.03dB
	Return loss (typical)	60dB or greater
	Splice time (typical)	6sec(SM G652 Quick Mode), 7sec(SM G652 Std. Mode), 8sec(Auto Mode)
	Heating time (typical)	14sec (FPS-61-2.6 sleeve, Slim 60mm Quick Mode)
	Splice & Heat cycles per battery full charge*2	Approx. 230 (BU-11)
	Fibre view & magnification	2 CMOS cameras observation, 320X (zoom : 700X) for X or Y single axis view, 88X for both X & Y dual axis view
	Proof test	1.96 ~ 2.09N
Programs	Applicable protection sleeve	60mm, 40mm & Sumitomo Nano sleeves
	Splice programs	Max. 300, 74 are pre-optimised, 226 editable by user
Functions	Heating programs	Max. 100, 24 are pre-optimised, 76 editable by user
	Splice image capture / Splice data storage	200 images / 10,000 splice data (internal memory only) 50,200/20,000 (with 8GB SD card)
	Attenuation splicing	0.1dB to 15dB in 0.1dB increments
	Universal clamps	Provided, 250µm, 900µm tight & loose buffer fibre
	Reversible coating clamps	Provided
	Dual automatic independent heaters	Provided
	User-selectable heater clamp operation	Provided
	Onboard user training video	Provided
	Automatic fibre identification	SMF / MMF / DSF / NZDSF / BIF / Other
	Automatic arc calibration	Automatically compensates for environmental condition changes
	Display of remaining Splice & Heat cycles	Provided (Battery mode)
	Wireless LAN connectivity (Option)*3	Provided
Size / Weight	Size	120(W) x 154(D) x 130(H) mm (without anti-shock rubber)
	Weight	1.8kg (without Battery) / 2.0kg (with Battery BU-11S) / 2.1kg (with Battery BU-11)
	Monitor	4.1" touch screen color LCD display
Terminals	DC output	DC 12V (for JR-6)
	USB port	USB 2.0 (mini-B type)
	Storage media	SD / SDHC memory card MAX32GB
Power supply	AC input	AC 100 ~ 240V, 50/60Hz (ADC-1430S)
	DC input	DC 10 ~ 15V
	Battery pack	Li-ion 11.1V, 2,300mAh (BU-11S) / Li-ion 11.1V, 4,600mAh (BU-11)
Operating condition		Altitude : 0 ~ 6,000m, Temperature : -10 ~ +50°C, Humidity : 0 ~ 95% (non-condensing), Wind velocity : up to 15m/sec
Storage condition		Temperature : -40 ~ +80°C, Humidity : 0 ~ 95% (non-condensing), Battery : -20 ~ +30°C (long term)
Electrode life *4		6,000 arc discharges
Software updates		Internet
Data management		Can be stored, edited and analyzed by dedicated PC software

*1 : Average value of the final inspection in room temperature with Sumitomo identical fibre. Measured by cut-back method relevant to ITU-T and IEC standards.

*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

*3 : Wireless LAN connectivity is not available in all countries. For more details, please refer to our Web site. <http://global-sei.com/sumitomo-electric-splicers/>

*4 : Achieved in lab condition. Electrode life may vary depending on the operating environment.

Environmental Durability*	
Test details	
Shock resistance	Drop from 76cm on 5 faces (excluding top face)
Water resistance	Equivalent to IPx2 (Operates normally after being exposed to water dripping at 3mm/min, for at least 2.5 min on each of 4 surfaces tilted at 15°)
Dust resistance	Equivalent to IP5x (Operates normally after 8 hours in a test chamber with circulating dust particles smaller than 75 µm²)

*Splicer operation after shock, water or dust tests, was confirmed under battery power, by Sumitomo.
Does not guarantee the product will not be damaged by these conditions.

Basic Accessories		
Part name	Part No.	Qty.
AC adapter	ADC-1430S	1 pc
AC power cord	PC-AC<X>*	1 pc
Cooling tray	—	1 pc
Spare electrode	ER-10	1 pair
Operating CD manual	—	1 pc
Quick reference guide	—	1 pc
Carrying case with worktable	CC-71+	1 pc
Hand strap	—	1 pc
USB cable	—	1 pc

*X=2(USA), 3(EU), 4(JP), 5(UK), 6(AUS), 7(South Africa)
Items listed in Basic Accessories are always included with the splicer body. Overall kit content may vary regionally. Please check with your local authorised reseller to confirm kit content in your region.



Carrying case with worktable
CC-71+




Handy cleaver
FC-8R series



Table-top cleaver
FC-6 / FC-6R series



Jacket remover
JR-M03



Available for
Lynx-Custom Fit™
Splice-On Connector



Electrode
ER-10

Accessories		
Part name	Part No.	Remarks
Accessories for Splicer	Wireless LAN SD card	WLSD-0308 For SumiCloud™ connection
	FHS-025	For φ0.25mm single fibre
	FHS-09	For φ0.9mm single fibre
	FHS-025/LB5	For 0.9mm loose buffered single fibre
	FHD-1	For drop/indoor cable(Cable size : typical 2.0 x 3.1 or 2.6mm)
	1SM-ST	For indoor cable (Cable size : typical 1.6 x 2.0mm)
	FHC-3	For 3mm cable
	Lynx2-UML-S	For φ3mm cord and φ0.9mm single fibre
	Battery pack	BU-11/11S Li-ion 4,600mAh BU-11, 2,300mAh BU-11S
	Battery charger	BC-11 —
Accessories	Car battery cable	PCV-11 For car battery operation (cigarette socket type)
	V-groove cleaning brush	VGT-2 Brush for cleaning V-groove
	Electrode	ER-10 —
	Handheld fibre cleaver	FC-8R-FC Automatic blade rotation cleaver with cleave counter
	FC-8R-F	Automatic blade rotation cleaver
	Fibre cleaver	FC-6S-C Table-top high precision cleaver
	FC-6RS-C	Automatic blade rotation cleaver
	Jacket remover	JR-M03 Jacket remover for single fibre
	Loose tube cutter	LTC-01 —
	Alcohol dispenser	HR-3 —
Fibre protection sleeve	FPS-1	60mm, diameter after shrink approx. φ3.2mm
	FPS-40	40mm, diameter after shrink approx. φ3.2mm
	FPS-61-2.6	61mm, diameter after shrink approx. φ2.6mm

SUMITOMO ELECTRIC INDUSTRIES, LTD.

Tokyo (Japan)
Sumitomo Electric Industries, Ltd.

Akasaka Center Building, 1-3-13, Motoakasaka,
Minato-ku, Tokyo, 107-8468, JAPAN
TEL: +81-3-6406-2666
<http://global-sei.com/sumitomo-electric-splicers/>

London (U.K.)
Sumitomo Electric Europe Ltd.

220 Centennial Park, Centennial Avenue, Elstree,
Herts. WD6 3SL, U.K.
TEL: +44 20-8953-8118
<http://www.sumielelectric.com/>

Dubai (U.A.E.)
Middle east office

Dubai Airport Free Zone Phase 4WA,
Office 702 P.O. Box 54890, Dubai, U.A.E.
TEL: +971 4-701-7338

Melbourne (Australia)
SWS Australia Pty. Limited

Oceania representative office
23 Scanlon Drive, Epping, Victoria, 3076,
AUSTRALIA
TEL: +61 3-8401-2800